

Type

Project

Notes



ADVANT
LIGHTING



AD-RPL

LED CEILING LIGHT

Direct/indirect capabilities with satin lens illumination

Sound absorption with felt panels available in 36 color options

Black/white exterior, 9 lip colors with dimming

5 YEARS
LIMITED WARRANTY
INCLUDED


IP44
RATED & TESTED



IESNA
LM-79

IESNA
LM-80

TECHNICAL DRAWING



AD-RPL-40/60: D Ø23.6" x H 5.5"

AD-RPL-90/120: D Ø35.4" x H 5.5"

AD-RPL-180/220: D Ø47.2" x H 5.5"

PRODUCT SPECIFICATIONS

Summary	AD-RPL-40	AD-RPL-90	AD-RPL-180
Dimensions	D Ø23.6" x H 5.5"	D Ø35.4" x H 5.5"	D Ø47.2" x H 5.5"
Lumen Output	3,400 lm (Down)	7,650 lm (Down)	15,300 lm (Down)
Efficacy	85 lm/W	85 lm/W	85 lm/W
Power Consumption	40 W (Down)	90 W (Down)	180 W (Down)
Summary	AD-RPL-60UD	AD-RPL-120UD	AD-RPL-220UD
Dimensions	D Ø23.6" x H 5.5"	D Ø35.4" x H 5.5"	D Ø47.2" x H 5.5"
Lumen Output	3,400 lm (Down) + 1,700 lm (Up)	6,120 lm (Down) + 4,080 lm (Up)	11,120 lm (Down) + 7,480 lm (Up)
Efficacy	85 lm/W	85 lm/W	85 lm/W
Power Consumption	40 W (Down) + 20 W (Up)	72 W (Down) + 48 W (Up)	132 W (Down) + 88 W (Up)
Input Voltage	120-277V AC		
CCT	3000K, 3500K, 4000K		
CRI	Ra80		
IP rating	IP44		
Lip Finish	Black, Green, Yellow, White, Blue, Silver, Red, Gold		
Finish	Black, White, *Acoustic Felt		
Working Temperature	-20° ~ 40°C		
Warranty	5 Years		



advantlighting.ca
(604) 207 9879

© Advant Lighting, LTD. All rights reserved. We reserve the right to change design, materials and finish in any way that will not alter installed appearance or reduce function and performance.

#105-8288 North Fraser Way,
Burnaby, BC V3N 0E9

Type

Project

Notes




ORDER FORM

AD-RPL		A		R80					
1	2	3	4	5	6	7	8	9	10
1. FAMILY	2. OUTPUT	2-A. UP/DOWN OUTPUT	3. VOLTAGE	4. CCT	5. CRI	6. DIMMING	7. FINISH		
AD-RPL	40 40 W 90 90 W 180 180 W	60UD 40 W + 20 W 120UD 72 W + 48 W 220UD 132 W + 88 W	A 120-277V AC	30 3000K 35 3500K 40 4000K	R80 Ra80	DM 0-10V TRI TRIAC	BK Black WH White AC *Acoustic Felt (Contact Us)		
8. LIP	9. LENS	10. INSTALLATION							
BK Black WH White GR Green YL Yellow	BL Blue SV Silver RD Red GD Gold	WH White SN Satin Nickel SP Suspended ST Stem SF Surface							


INSTALLATION OPTIONS

Suspended




AD-RPL-40/60UD: D Ø23.6" x H 5.5" (A Ø10" x B 1.38")
AD-RPL-90/120UD: D Ø35.4" x H 5.5" (A Ø10" x B 1.38")
AD-RPL-180/220UD: D Ø47.2" x H 5.5" (A Ø13.8" x B 1.38")

Stem



AD-RPL-40/60UD: D Ø23.6" x H 5.5" (A Ø5" x B 1.4")
AD-RPL-90/120UD: D Ø35.4" x H 5.5" (A Ø5" x B 1.4")
AD-RPL-180/220UD: D Ø47.2" x H 5.5" (A Ø5" x B 1.4")

Surface



AD-RPL-40/60UD: D Ø23.6" x H 6.9"
AD-RPL-90/120UD: D Ø35.4" x H 6.9"
AD-RPL-180/220UD: D Ø47.2" x H 6.9"