



### **AP-AV3SSF**

### Ultra-Thin Profile Square Regressed Shower Trim

Housing-free light engine install quickly.

The perfect option for a flush finish with ceiling materials.

Ease of installation, fast-mount features.












### **TECHNICAL DRAWING**







TR - Flangeless Trim

Units in Metric

### **PRODUCT SPECIFICATIONS**

Summary	AP-AV3SSF-AR	AP-AV3SSF-TR
Dimensions	105mm x 105mm x 155mm	89mm x 89mm x 155mm
<b>Power Consumption</b>	14 W, 23 W	14 W, 23 W
Lumen Output	1050 - 1550 lm	1050 - 1550 lm
Input Voltage	120-277V AC	120-277V AC
Colour Temperature	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K
Finish	Gold, Chrome, Brushed Chrome, Matte White, Brushed Nickel, Sa	atin Nickel, Matte Black, Aluminum
CRI	Ra90	Ra90
Beam Angle	44° (Flood)	44° (Flood)
Warranty	5 Years	5 Years

### **ORDER FORM**

1	2 3	4	5 6	5 7	8
1. FAMILY	2. SIZE	3. WATTAGE	4. VOLTAGE	5. CCT	
AP-AV3SSF	<b>AR</b> 105 x 105 x 155 <b>TR</b> 89 x 89 x 155	14 14W 23 23W	<b>A</b> 120-277V AC		3500K 4000K
6. BEAM ANGLE	7. DIMMING	8. FINISH			
<b>44</b> 44°	<ul><li>DM 0-10V Dimming</li><li>TRI TRIAC Dimming</li></ul>		BC Brushed Chrome WH BN Brushed Nickel BK	Mhite <b>GD</b> Gold Black <b>SN</b> Satin Ni	ickel



## **OPTIONS & ACCESSORIES**

### **MOUNTING PLATE**

Ideal for unfinished basements and other renovation projects. Choice of Square or Round for 3.5" Remodel housings. Adjustable mounting bars included.



PA3NW 3.5" Sqaure, 3.5" Round

### **EMERGENCY DRIVER**

Battery life: 120 minutes

Available only for 3.5" and 4" New Construction housings.

Housing Option: -EM suffix





# STEP-DOWN TRANSFORMER

Available only for 3.5" and 4" Remodel and New Construction housings.

STD-60M 3.5"

3.5" Sqaure, 3.5" Round



### **LENSES**

Choice of replacement lenses for on-site modification of light diffusion. Shower Light trims available only with Frosted lens.

\*Wall Wash trims available only with Frosted/Frosted lens.

















# **HOUSINGS**



### **IC AIR TIGHT HOUSING - ROUND**

	ICAT		6		R		3		V		
1. MOI	DEL	2.	HOUSING	3.	TYPE	4.	SERIES	5.	DRIVER	6. F	PERFORMANCE
ICAT	Insulated Housing Air Tight	6	410 x 254 (16" x 10")	R	Round	3	3-1/2"	٧	120-277V AC		14 W 1300 lm 23 W 1900 lm



### **IC AIR TIGHT HOUSING - SQUARE**

	ICAT		6		S			3		V		
1. MOI	DEL	2.	HOUSING	3.	TYPE		4. \$	SERIES	5.	DRIVER	6. F	PERFORMANCE
ICAT	Insulated Housing Air Tight	6	410 x 254 (16" x 10")	s	Square	;	3	3-1/2"	V	120-277V AC	14 23	



### **REMODEL HOUSING**

	REA	3	S	
1. MO	DEL	2. SERIES	3. DRIVER	4. PERFORMANCE
REA	Remodel Housing	<b>3</b> 3-1/2"	<b>V</b> 120-277V AC	1 1300 lm (1000 lm with 2-1/2") 2 1900 lm L WD or CT

CT: Colour Tuning WD: Warm Dimming



### **NEW CONSTURCTION HOUSING**

NWA			3	V			
1. MODEL	2. TYPE	3. SERIES	4. DRIVER	5. PER	RFORMANCE	6. 0	OPTIONS
NWA New Construction Housing	S Square R Round	<b>3</b> 3-1/2"	<b>V</b> 120-277V	2 1	300 lm 1000 lm with 2-1/2") 900 lm VD or CT		Emergency Driver (not available with WD and CT)



### IC INSULATED HOUSING

	ISA					3			V		
1. MC	DEL	2.	TYPE	3.	SERIES		4. D	RIVER		5. I	PERFORMANCE
ISA	Insulated Housing	S R	Square Round	3	3-1/2"		V	120-277V A	С	1 2 L	1300 lm (1000 lm with 2-1/2") 1900 lm WD or CT